



FaceStation – Access Control / Time and attendance

Features:

- Intelligent Face Recognition Technology
 - Allows fast & easy recognition with higher security
 - Embedded Web Server
 - Preloaded with BioStar Lite embedded web server
 - Versatile Interfaces
 - PoE, WiFi, TCP/IP, RS485/232, Wiegand, relay
 - Built-in Card Reader
- Intuitive Touch Screen GUI
 - 4.3” touchscreen LCD with easy-to-use GUI
 - Ultra Performance
 - Covers up to 10,000 users with powerful dual CPU
 - Video Phone
 - IP based video and audio interface or analog video phone
 - 13.56MHz Mifare/DesFire

Specifications:

CPU	1.1 GHz DSP, 667MHz RISC
Memory	4GB ash, 512MB RAM
LCD	4.3 inch WVGA touch screen
Camera	Face recognition, face log, videophone
RF Card Options	13.56MHz Mifare/DesFire
Template Capacity	10,000 (1:1), 1,000 (1:N)
Max User	10,000
Log Capacity	1,000,000 / 10,000 image logs
PoE	Yes
Interfaces	Wireless LAN(optional), TCP/IP, Wiegand 2ch RS485, RS232, 4 x TTL I/O, 2 x Relay USB (Host & Slave)
Tamper	Switch
Sound	16 bit Hi-Fi voice & sound indication
Operating Temp	- 20°C ~ 50°C
Operating Voltage	12V DC
Dimensions (mm)	132(W) x 165(H) x 60(D)
Certificates	CE, FCC, KCC, RoHS